

New Type	Old Type	Dimension (mm)						Reference Dimension (mm)				
		D	H	a	2 α	2 β	2 γ	h	h1	h2	R	E
S40-0161214-1.8	40-1.8	16	12	1.8	14°	40°	60°	1.0	1.5	5.0	1.5	1.0
S40-0161214-2.4	40-2.4	16	12	2.4	14°	40°	60°	1.0	1.5	5.0	1.5	1.0
S40-0221814-2.8	40-2.8	22	18	2.8	14°	40°	60°	1.5	2.0	7.0	2.0	1.2
S40-0221814-3.2	40-3.2	22	18	3.2	14°	40°	60°	1.5	2.0	7.0	2.0	1.2
S40-0221814-3.6	40-3.6	22	18	3.6	14°	40°	60°	1.5	2.0	7.0	2.0	1.2
S40-0221814-4.0	40-4.0	22	18	4.0	14°	40°	60°	1.5	2.0	7.0	2.0	1.2
S40-0302114-4.6	40-4.6	30	21	4.6	14°	40°	60°	2.0	2.0	11.0	3.0	1.5
S40-0302114-5.0	40-5.0	30	21	5.0	14°	40°	60°	2.0	2.0	11.0	3.0	1.5
S40-0302114-5.7	40-5.7	30	21	5.7	14°	40°	60°	2.0	2.0	11.0	3.0	1.5
S40-0302114-6.7	40-6.7	30	21	6.7	14°	40°	60°	2.0	2.0	11.0	3.0	1.5
S40-0352514-7.7	L40-7.7	35	25	7.7	14°	40°	60°	3.0	3.0	13.0	3.0	1.5
S40-0352514-8.7	L40-8.7	35	25	8.7	14°	40°	60°	3.0	3.0	13.0	3.0	1.5
S40-0352514-9.7	40-9.7	35	25	9.7	14°	40°	60°	3.0	3.0	13.0	3.0	1.5
S40-0452514-10.7	L40-10	45	25	10.7	14°	40°	60°	3.5	3.0	13.0	4.0	1.5
S40-0452514-11.7	40-11	45	25	11.7	14°	40°	60°	3.5	3.0	13.0	4.0	1.5
S40-0452514-12.7	40-12	45	25	12.7	14°	40°	60°	3.5	3.0	13.0	4.0	1.5
S40-0452514-13.7	40-13	45	25	13.7	14°	40°	60°	3.5	3.0	13.0	4.0	1.5
S40-0452514-14.7	40-14	45	25	14.7	14°	40°	60°	3.5	3.0	13.0	4.0	1.5
S40-0502814-15.7	L40-15	50	28	15.7	14°	40°	60°	4.0	3.0	14.0	4.0	1.5
S40-0502814-16.7	40-16	50	28	16.7	14°	40°	60°	4.0	3.0	14.0	4.0	1.5
S40-0502814-17.7	40-17	50	28	17.7	14°	40°	60°	4.0	3.0	14.0	4.0	1.5
S40-0502814-18.7	L40-18	50	28	18.7	14°	40°	60°	4.0	3.0	14.0	4.0	1.5
S40-0552818-18.9	S40-18	55	28	18.9	18	40	60	4.0	3.0	12.0	6.0	1.5
S40-0602118-6.7	40-6.7	60	21	6.7	18	40	60	9.0	2.5	9.0	5.5	1.5
S40-0603016-19.7	L40-19	60	30	19.7	16°	40°	60°	5.0	4.0	14.0	4.0	1.5
S40-0603016-20.7	40-20	60	30	20.7	16°	40°	60°	5.0	4.0	14.0	4.0	1.5
S40-0603016-21.7	L40-21	60	30	21.7	16°	40°	60°	5.0	4.0	14.0	4.0	1.5
S40-0603016-22.7	40-22	60	30	22.7	16°	40°	60°	5.0	4.0	14.0	4.0	1.5
S40-0603016-23.7	40-23	60	30	23.7	16°	40°	60°	5.0	4.0	14.0	4.0	1.5
S40-0653216-24.7	40-24	65	32	24.7	16°	40°	60°	6.0	5.0	14.0	5.0	1.5
S40-0653216-25.5	40-25	65	32	25.5	16°	40°	60°	6.0	5.0	14.0	5.0	1.5
S40-0653216-26.5	40-26	65	32	26.5	16°	40°	60°	6.0	5.0	14.0	5.0	1.5
S40-0653216-27.5	40-27	65	32	27.5	16°	40°	60°	6.0	5.0	14.0	5.0	1.5
S40-0703516-28.5	40-28	70	35	28.5	16°	40°	60°	8.0	6.0	16.0	5.0	1.5
S40-0703516-29.5	40-29	70	35	29.5	16°	40°	60°	8.0	6.0	16.0	5.0	1.5
S40-0703516-30.5	40-30	70	35	30.5	16°	40°	60°	8.0	6.0	16.0	5.0	1.5
S40-0703516-31.5	40-31	70	35	31.5	16°	40°	60°	8.0	6.0	16.0	5.0	1.5
S40-0803516-32.5	40-32	80	35	32.5	16°	40°	60°	8.0	6.0	16.0	5.0	2.0
S40-0803516-33.5	40-33	80	35	33.5	16°	40°	60°	8.0	6.0	16.0	5.0	2.0
S40-0803516-34.5	40-34	80	35	34.5	16°	40°	60°	8.0	6.0	16.0	5.0	2.0

S40-0803516-35.5	40-32	80	35	35.5	16°	40°	60°	8.0	6.0	16.0	5.0	2.0
S40-0803516-36.5	40-36	80	35	36.5	16°	40°	60°	8.0	6.0	16.0	5.0	2.0
S40-0803516-37.5	40-37	80	35	37.5	16°	40°	60°	8.0	6.0	16.0	5.0	2.0
S40-0904020-38.5	40-38	90	40	38.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-0904020-39.5	40-39	90	40	39.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-0904020-40.5	40-40	90	40	40.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-0904020-41.5	40-41	90	40	41.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1004020-42.5	40-42	100	40	42.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1004020-44.5	40-44	100	40	44.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1004020-47.5	40-42	100	40	47.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1104020-44.7	S40-44-110	110	40	44.7	20	40	60	7.4	6	16	7	1.5
S40-1204520-49.5	40-49	120	45	49.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1204520-51.5	40-51	120	45	51.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1204520-53.5	40-53	120	45	53.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0
S40-1204520-54.5	40-54	120	45	54.5	20°	40°	60°	8.0	6.0	16.0	6.0	2.0