

New Type	Old Type	Dimension (mm)						Reference Dimension (mm)				
		D	H	s	2 $\alpha$	2 $\beta$	2 $\gamma$	h	h1	h2	R	e
S60-0252021-2.5	V60-2.5H	25	20	2.5	21°	40°	60°	1.7	3.0	12.0	3.3	1.2
S60-0302114-2.5	L60-2.5	30	21	2.5	14°	40°	60°	1.8	2.0	9.0	4.0	1.2
S60-0302114-3.0	L60-3.0	30	21	3.0	14°	40°	60°	1.8	2.0	9.0	4.0	1.2
S60-0252021-3.5	V60-3.5H	25	20	3.5	21°	40°	60°	1.7	3.0	12.0	3.3	1.2
S60-0302114-4.0	L60-4.0	30	21	4.0	14°	40°	60°	1.8	2.0	9.0	4.0	1.2
S60-0252021-4.5	V60-4.5H	25	20	4.5	21°	40°	60°	1.7	3.0	12.0	3.3	1.2
S60-0302114-4.7	L60-4.7	30	21	4.7	14°	40°	60°	2.5	2.0	9.0	4.0	1.2
S60-0292022-5.5	V60-5.5H	29	20	5.5	22°	40°	60°	2.0	3.0	12.0	3.0	1.2
S60-0302114-5.7	L60-5.7	30	21	5.7	14°	40°	60°	2.5	2.0	9.0	4.0	1.2
S60-0251335-6.0	V60-6.0-25	25	13	6.0	35°	40°	60°	1.8	2.0	7.5	2.0	1.2
S60-0251335-6.0H	V60-31.8H	25	13.9	6.0	35°	40°	60°	2.6	2.0	7.5	2.0	1.5
S60-0292022-6.5	V60-6.5H	29	20	6.5	22°	40°	60°	2.0	3.0	12.0	3.0	1.2
S60-0302114-6.7	L60-6.7	30	21	6.7	14°	40°	60°	2.5	2.0	9.0	4.0	1.2
S60-0292022-7.5	V60-7.5H	29	20	7.5	22°	40°	60°	2.0	3.0	12.0	3.0	1.2
S60-0302114-7.7	L60-7.7	30	21	7.7	14°	40°	60°	2.5	2.0	9.0	4.0	1.2
S60-0342023-8.5	V60-8.5H	34	20	8.5	23°	40°	60°	2.3	3.0	12.0	2.7	1.2
S60-0352114-8.7	L60-8.7	35	21	8.7	14°	40°	60°	3.0	2.0	9.0	4.0	1.2
S60-0342022-9.5	LH-145	34	20	9.5	22°	40°	60°	1.8	3.0	12.0	3.2	1.2
S60-0342023-9.5	V60-9.5H	34	20	9.5	23°	40°	60°	2.3	3.0	12.0	2.7	1.2
S60-0352114-9.7	L60-9.7	35	21	9.7	14°	40°	60°	3.0	2.0	9.0	4.0	1.2
S60-0342023-10.5	V60-10.5H	34	20	10.5	23°	40°	60°	2.3	3.0	12.0	2.7	1.2
S60-0352114-10.6	L60-10	35	21	10.6	14°	40°	60°	3.0	2.0	9.0	4.0	1.2
S60-0382324-11.5	V60-11.5H	38	23	11.5	24°	40°	60°	2.6	3.0	14.0	3.4	1.5
S60-0402514-11.5	L60-11	40	25	11.5	14°	40°	60°	3.5	3.0	12.5	4.0	1.5
S60-0382324-12.5	V60-12.5H	38	23	12.5	24°	40°	60°	2.6	3.0	14.0	3.4	1.5
S60-0402514-12.5	L60-12	40	25	12.5	14°	40°	60°	3.5	3.0	12.5	4.0	1.5
S60-0432423-13.5	LH-146	43	24	13.5	23°	40°	60°	2.5	3.5	14.0	4.0	1.5
S60-0432424-13.5	V60-13.5H	43	24	13.5	24°	40°	60°	3.0	3.5	14.0	3.5	1.5
S60-0452514-13.5	L60-13	45	25	13.5	14°	40°	60°	4.0	3.0	13.0	4.0	1.5
S60-0432424-14.5	V60-14.5H	43	24	14.5	24°	40°	60°	3.0	3.5	14.0	3.5	1.5
S60-0452514-14.5	L60-14	45	25	14.5	14°	40°	60°	4.0	3.0	13.0	4.0	1.5
S60-0442424-15.5	V60-15.5H	44	24	15.5	24°	40°	60°	3.0	3.5	14.0	3.5	1.5
S60-0452514-15.5	L60-15	45	25	15.5	14°	40°	60°	4.0	3.0	13.0	4.0	1.5
S60-0442424-16.5	V60-16.5H	44	24	16.5	24°	40°	60°	3.0	3.5	14.0	3.5	1.5
S60-0452514-16.5	L60-16	45	25	16.5	14°	40°	60°	4.0	3.0	13.0	4.0	1.5
S60-0452424-17.5	V60-17.5H	45	24	17.5	24°	40°	60°	3.0	3.5	14.0	3.5	1.5
S60-0452514-17.5	L60-17	45	25	17.5	14°	40°	60°	4.0	3.0	13.0	4.0	1.5
S60-0452424-18.5	V60-18.5H	45	24	18.5	24°	40°	60°	3.0	3.5	14.0	3.5	1.5
S60-0452514-18.5	L60-18	45	25	18.5	14°	40°	60°	4.0	3.0	13.0	4.0	1.5
S60-0532724-19.5	V60-19.5H	53	27	19.5	24°	40°	60°	3.0	4.0	16.0	4.0	1.5

S60-0552814-19.5	L60-19	55	28	19.5	14°	40°	60°	5.0	4.0	14.0	5.0	1.5
S60-0532323-20.5	LH-147	53	23	20.5	23°	40°	60°	2.5	4.0	16.0	4.5	1.5
S60-0532724-20.5	V60-20.5H	53	27	20.5	24°	40°	60°	3.0	4.0	16.0	4.0	1.5
S60-0552814-20.5	L60-20	55	28	20.5	14°	40°	60°	5.0	4.0	14.0	5.0	1.5
S60-0532724-21.5	V60-21.5H	53	27	21.5	24°	40°	60°	3.0	4.0	16.0	4.0	1.5
S60-0552814-21.5	L60-21	55	28	21.5	14°	40°	60°	5.0	4.0	14.0	5.0	1.5
S60-0532723-22.5	LH-148	53	27	22.5	23°	40°	60°	2.5	4.0	16.0	4.5	1.5
S60-0552724-22.5	V60-22.5H	55	27	22.5	24°	40°	60°	3.0	4.0	16.0	4.0	1.5
S60-0552814-22.5	L60-22	55	28	22.5	14°	40°	60°	5.0	4.0	14.0	5.0	1.5
S60-0552724-23.5	V60-23.5H	55	27	23.5	24°	40°	60°	3.0	4.0	16.0	4.0	1.5
S60-0552814-23.5	L60-23	55	28	23.5	14°	40°	60°	5.0	4.0	14.0	5.0	1.5
S60-0602816-24.5H	L60-24H	60	28	24.5	16°	40°	60°	6.0	3.5	13	4.2	1.5
S60-0632924-24.5	V60-24.5H	63	29	24.5	24°	40°	60°	3.5	4.0	17.5	4.0	1.5
S60-0653016-24.5	L60-24	65	30	24.5	16°	40°	60°	6.0	4.5	14.0	5.0	1.5
S60-0632924-25.5	V60-25.5H	63	29	25.5	24°	40°	60°	3.5	4.0	17.5	4.0	1.5
S60-0653016-25.5	L60-25	65	30	25.5	16°	40°	60°	6.0	4.5	14.0	5.0	1.5
S60-0632924-26.5	V60-26.5H	63	29	26.5	24°	40°	60°	3.5	4.0	17.5	4.0	1.5
S60-0653016-26.5	L60-26	65	30	26.5	16°	40°	60°	6.0	4.5	14.0	5.0	1.5
S60-0652924-27.5	V60-27.5H	65	29	27.5	24°	40°	60°	3.5	4.0	17.5	4.0	1.5
S60-0653016-27.5	L60-27	65	30	27.5	16°	40°	60°	6.0	4.5	14.0	5.0	1.5
S60-0652924-28.5	V60-28.5H	65	29	28.5	24°	40°	60°	3.5	4.0	17.5	4.0	1.5
S60-0653016-28.5	L60-28	65	30	28.5	16°	40°	60°	6.0	4.5	14.0	5.0	1.5
S60-0703024-29.5	V60-29.5H	70	30	29.5	24°	40°	60°	3.8	4.0	17.5	4.7	1.5
S60-0703024-29.5H	V60-29.5H	70	30	29.5	24°	40°	60°	3.8	4.0	17.5	4.7	1.5
S60-0703024-31.5H	V60-31.5H	70	30	31.5	24°	40°	60°	3.8	4.0	17.5	4.7	1.5
S60-0753516-29.5	L60-29	75	35	29.5	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-30.5	L60-30	75	35	30.5	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0703024-31.5	V60-31.5H	70	30	31.5	24°	40°	60°	3.8	4.0	17.5	4.7	1.5
S60-0753516-31.3	L60-31	75	35	31.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-32.3	L60-32	75	35	32.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753524-33.5	V60-33.5H	75	35	33.5	24°	40°	60°	4.0	5.5	19.5	6.0	1.5
S60-0753516-33.3	L60-33	75	35	33.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-34.3	L60-34	75	35	34.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-35.3	L60-35	75	35	35.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-36.3	L60-36	75	35	36.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-37.3	L60-37	75	35	37.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0903516-38.3	L60-38	90	35	38.3	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-39.3	L60-39	90	35	39.3	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-41.0	L60-41	90	35	41.0	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-42.0	L60-42	90	35	42.0	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-44.0	L60-44	90	35	44.0	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-47.0	L60-47	90	35	47.0	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-49.0	L60-49	90	35	49.0	16°	40°	60°	7.0	5.0	15.0	6.0	2.0

S60-1004016-52.0	L60-52	100	40	52.0	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1004016-54.0	L60-54	100	40	54.0	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1004016-57.0	L60-57	100	40	57.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-59.5	L60-59	120	42	59.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-61.5	L60-61	120	42	61.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-64.5	L60-64	120	42	64.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-67.5	L60-67	120	42	67.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-70.5	L60-70	120	42	70.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-74.5	L60-74	120	42	74.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-0753516-29.5	L60-29	75	35	29.5	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-30.5	L60-30	75	35	30.5	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-31.3	L60-31	75	35	31.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-32.3	L60-32	75	35	32.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-33.3	L60-33	75	35	33.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753524-33.5H	V60-33.5H	75	35	33.5	24°	40°	60°	7.0	5.0	19.5	6.0	1.5
S60-0753516-34.3	L60-34	75	35	34.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-35.3	L60-35	75	35	35.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-36.3	L60-36	75	35	36.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0753516-37.3	L60-37	75	35	37.3	16°	40°	60°	7.0	5.0	15.0	6.0	1.5
S60-0903516-38.3	L60-38	90	35	38.3	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-39.3	L60-39	90	35	39.3	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-40.0	L60-40	90	35	40	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-41.0	L60-41	90	35	41	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-42.0	L60-42	90	35	42	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-43.0	L60-43	90	35	43	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-44.0	L60-44	90	35	44	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-47.0	L60-47	90	35	47	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-0903516-49.0	L60-49	90	35	49	16°	40°	60°	7.0	5.0	15.0	6.0	2.0
S60-1004018-49	S60-49-100	100	40	49	18°	40°	60°	8.5	6.0	13.0	6.0	2.0
S60-1004016-52	60-52H	100	40	52	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1004016-52.0	L60-52	100	40	52	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1004016-54.0	L60-54	100	40	54	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1104018-54	S60-54	110	40	54	18°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-59	S60-59-120	120	42	59	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-59.5	L60-59	120	42	59.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-61.5	L60-61	120	42	61.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-64.5	L60-64	120	42	64.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-67.5	L60-67	120	42	67.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-70.5	L60-70	120	42	70.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0
S60-1204216-74.5	L60-74	120	42	74.5	16°	40°	60°	8.0	6.0	16.0	6.0	2.0